

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Milk Coolers - Dual Sided Door

Milk Coolers Super Deluxe Series

Model: TMKC-49-2-WS-N6



___ FEATURES & BENEFITS =__

■ Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology. Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Convenient bottom floor drain standard with hose adapter

Floor drain is located in the rear on the right hand side for easy clean out. The hose adapter allows for convenient connecting to drain hose.

Extended cleaning-free condenser

Electrodeposition coating is applied to prevent condenser corrosion, and wire condenser are applied to prevent dust from accumulating.

■ Sturdy and clean, durable cabinet construction Exterior is made of white coated steel with stainless steel interior and

Exterior digital thermometer standard for easy visibility

Exterior digital temperature display allows easy reading and precise and constant temperature. This level of precision allows milk to remain fresh and safe over an extended period of time.

■ High-density polyurethane insulation

The entire cabinet construction is foamed-in-place using high density, environmental friendly CFC free polyurethane insulation.

- Stainless steel self-service doors have drop front feature and hold-open flip-up top lid
- 4" dia. swivel casters standard for easy movement, two with brakes to lock the unit in place
- Refrigerator holds 33°F ~ 38°F for the best in milk preservation

Direct cooling type









Model	# of Doors	# of Floor Rack	CU./FT.	Crate Capacity (13 x 13 x 11-5/8)	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
TMKC-49-2-WS-N6	4	2	18.3	12	1/5	7	352	49 x 327/8 x 405/8

doors

Milk Coolers - Dual Sided Door

Model: TMKC-49-2-WS-N6

SPECIFICATIONS					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	7				
Compressor HP	1/5				
Cord Length (ft.)	9				
Refrigerant	R-600a				
Net Capacity (cu. ft.)	18.3				
Ext. Length (in.)	49 (1245mm)				
Ext. Depth (in.) *	327/8 (836mm)				
Ext. Height (in.)†	405/8 (1031mm)				
# of Doors	4				
Crate Capacity (13" x 13" x 115/8")	12				
Gross Weight (lbs.)	352				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

3 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor


STANDARD FEATURES

- Door locks standard
- · Heavy duty floor racks standard
- · Door support bumpers standard


OPTIONAL ACCESSORIES

• Corner bumpers (4pcs/set): K345201160

PLAN VIEW (unit: inch)



TOP VIEW



Ver.20200928









■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









^{*} Depth does not include 1-3/8" for door support bumpers.

[†] Height does not include 1-1/4" for door handles and door support bumpers.